



φ=30°仕様 (FLW-II B) 背面土及び基礎地盤の内部摩擦角φ30≥30°に適用。

呼び名	参考重量 (kg)	寸法 (mm)														
		H	B	h	H ₁	D ₁	D ₂	T ₁	T ₂	i	K	a	b	c	d	e
750	650	750	550	640	—	110	103	110	110	8	110	150	—	175	600	500
1,000	856	1,000	700	890	—	110	101	110	110	10	110	150	—	325	600	500
1,200	1,054	1,200	850	1,090	200	110	110	110	110	12	110	150	—	300	600	500
1,250	1,080	1,250	850	1,140	250	110	110	110	110	13	110	150	—	450	600	500
1,400	1,239	1,400	1,000	1,290	400	110	110	110	110	14	100	150	—	450	600	500
1,500	1,291	1,500	1,000	1,390	500	110	110	110	110	15	110	150	—	450	600	500
1,600	1,702	1,600	1,150	1,450	100	110	118	150	150	16	150	150	650	450	650	500
1,750	1,780	1,750	1,150	1,600	250	110	118	150	150	18	150	150	650	450	650	500
1,800	1,890	1,800	1,300	1,650	300	110	113	150	150	18	150	150	650	600	650	500
2,000	1,994	2,000	1,300	1,850	500	110	113	150	150	20	150	150	650	600	650	500
2,200	2,603	2,200	1,450	2,020	200	120	130	180	180	22	180	150	650	600	650	500
2,250	2,632	2,250	1,450	2,070	250	120	130	180	180	23	180	150	650	600	650	500
2,400	2,810	2,400	1,600	2,020	400	120	124	180	180	24	180	150	650	750	650	500
2,500	2,868	2,500	1,600	2,320	500	120	124	180	180	25	180	150	650	750	650	500
2,600	3,566	2,600	1,750	2,380	100	120	134	220	220	26	220	150	800	750	800	500
2,750	3,653	2,750	1,750	2,530	250	120	134	220	220	28	220	150	800	750	880	500
2,800	3,777	2,800	1,900	2,580	100	120	126	220	220	28	220	150	800	900	880	500
3,000	3,892	3,000	1,900	2,780	300	120	126	220	220	30	220	150	800	900	880	500

- 注意 ●高さを上表の規格外とする場合は、その他の項目については高さが直近上位の規格を準用します。
- 長さを上表の規格外とする場合は、1mまでこれを縮小することができます。